NUVICO[®]





Server Based 32ch NVR SN-P3200, SN-U3200

Key Features

- Records up to 32 IP cameras 10pps @ 2MP per channel
- 4ch pro license included
- Plug & Record configuration with Dual Gbit ports
- Built-in DVD burner or USB flashdrive
- 4 Removable HDD bays
- Local Monitors: HDMI, DVI, VGA
- Hardware RAID (SN-U3200)
- 50 Brands, over 2000 models + Onvif IP cameras are supported
- Advanced Video Analytics
- No HDD included for SN-P3200

Supported IP Camera Vendors

ACTi	ADT	Arecont	ARM	Axis	Basler	Bosch	Brickcom	Camtron	Centrix
Cisco	CNB	Crypto	Digimerge	Dallmeier	Dahua	D-Link	Dynacolor	GE	Honeywell
Icantek	IQinVision	JVC	LG	Lilin	Linksys	Lemenera	Messea	Micronet	MOBOTIX
Panasonic	Planet	Pelco	Probe	Samsung	StarDot	Santec	Telecom	TRUEN	TOSHIBA
VIVOTEK	Zavio	3 Svision							









GE Security















VIVOTEK

Technical Specifications

NUVICO Server Based ONVIF NVR Series						
Part number	SN-P3200	SN-U3206				
Video Compression	Н.264					
Licenses Included	4ch Licenses Included					
Compatible License type	Pro License					
Additional License Option	Up to 32ch, 10pps @ 2MP					
Max Recording MP	65MP					
CPU / Case Type	Core i7 / 4U Case					
HDD Case Type	4 Removable Bays					
RAM	8GB DDR 3					
Video Output	HDMI, VGA, DVI					
OS	Windows7 on Built-in SSD for Maximum Stability					
OS DRIVE	120GB Intel SSD					
Included HDD	No HDD	6TB Inlcuded				
RAID INFO	N/A	Dedicated H/W RAID Card				
Optical Drive	DVD-RW					
External Copy Device	USB Flashdrive (Max 2GB Clips)					
Network Interface	2 x Gbit ports					
Audio Over Network	2-way					
PTZ Dome & Controller Interface	Yes					
Recording Modes	Continuous, Schedule, Motion, and Video Analytics					
Pre-event & Post-event Recording	Pre-recording: 3 sec. per channel / Post-recording: 240 sec. per channel					
Search Mode	Time / Calender / Event Search / Video Analytics					
Video Analytics	Advanced Video Analytics					
DPTZ	8 Ways, Up to 64 times					
IP Camera Compatible List	50 Brands over 2000 models + Onvif					
Watermark	Yes					
Rack Mount Kit	Yes					
Warranty	3 years					
Operating Temperature	41°F ~ 104°F (0°C ~ +40°C)					
power Input	AC 100 ~ 240V, 50/60 Hz, 170W Max, Typical 120W					
IP Cam Inputs	64 CH					
Stream Profiles	Customizable					
E-map Support	10 Layers					
Playback	16 CH					
Remote Clients	Multiple Server (Sites)					
Remote Live Viewer	128 CH					
Remote Playback	16 CH					
CMS	YES					
POS	YES					
SDK	YES					
Colunting Application	YES					

SN-P3200/SN-U3200

Accessories

SN-URB20	2TB HDD bay kit		
SN-URB30	3TB HDD bay kit		
SN-URB40	4TB HDD bay kit		
SN-4LP	4ch additional license pack for SN-P, SN-U Series		
SN-4AC*	4ch Analog capture card (limited 1 capture card per system)		
SN-8AC*	8ch Analog capture card (limited 1 capture card per system)		
*One analog port option per system			